








»» Rotary And Cutting Teeth

KEMAICO USA CORPORATION

Globe Drilling Industry Experts

Just tell us whatever you need, our special tailored is waiting for you upon your demand

Rotary teeth include sediment type, efficiency type, durable type, attack type and tooth seat series.
The products mainly use high-quality high-performance alloy teeth, advanced welding technology, reasonable heat treatment process, reasonable design, fast excavation, longer service life.

Category	Type	Application	image
Sediment type series	TY3050-19A1-C	Suitable for the very soft sediment and the mining industry, not allowed into the rock	
Efficiency series	JC3050L-19B2-C	1.Suitable for sandstone, pebbles and limestone below 30MPa;	
		2.High drilling efficiency;	
	JC3060L-22B2-C	1. Suitable for sandstone, pebbles, caves and limestone below 50MPa;	
		2. High drilling efficiency;	
Durable series	JC3050-19B2-C/S	The king of limestone cost	
	JC3050-22B2-C/S	The king of cost-effective basalt, Granite, for 40MPa the	
	JC3055-19B2-C/S	The king of Sandstone cost	
	JC3055-22B2-C/S	Granite, for 60MPa the following rock	
	JC3055-25B2-C/S	Caves Caves, specializing in karst caves or fractured rock conditions	
	JC3060-22B2-C/S	The king of pebbles, cobblestone conditions ace products.	
	JC3060-25B2-C/S	Granite, basalt nemesis, for more than 60MPa rock.	
Tackling series	HT3050-19C-C/S HT3055-22C-C/S	1、Tackle tough, any complex and large loss of rotary gear teeth can be applied to the working conditions.	
	HT3060-22C-C/S	2.Excellent wear and rotation of	
	HT3060-25C-C/S	trouser body performance, drastically improve drilling efficiency and reduce	
Tooth seat series	68-95 circular gear seat	Wear-resistant round tooth seat	
	78-95 round tooth seat		
	B43 square tooth seat	Wear-resistant square-shaped seat	

Notes:

TY3050-19A1-C

TY: Sand Series 30: Shank Diameter 50: Big Head Diameter 19: Alloy Diameter A1: Wear Resistant Coating Material C: Alloy Teeth Grade.

JC3050-19B2-C/S

JC: Durable Series 30: Shank Diameter 50: Big Head Diameter 19: Alloy Diameter B2: Wear Resistant Coating Material C / S: Alloy Teeth Grade.

HT3050-19C-C/S

HT: Hardening Series 30: Shank Diameter 50: Big Head Diameter 19: Alloy Diameter C: Alloy Body Care C / S: Alloy Teeth Grade.

Cutting teeth, including ordinary asphalt series, modified asphalt series, cement pavement series and cold regeneration series. Products using the most advanced production technology, the highest quality raw materials, with good wear resistance, strong impact toughness, long life, high operating efficiency.

Category	Type	Application	Image
Ordinary asphalt series	PT01	Suitable for the repair of ordinary asphalt pavement milling	
Modified asphalt series	GX01	Suitable for the repair of modified asphalt pavement	
Cement Pavement Series	SN01	Suitable for cement road and water mixed layer milling repair	
Cold regeneration series	ZS01	Suitable for cold regeneration series machines	

Notes:

PT: Ordinary asphalt GX: Modified asphalt SN: Cement concrete pavement ZS: Cold regeneration
01: General type, suitable for most of the corresponding conditions.
PT, GX, cement are 20 shank diameter, ZS is 22 shank diameter, when used with the attention of the gear seat.



Rotating Teeth



Cutting Teeth





KEMAICO USA CORPORATION

Address: 300 Knightsbridge Pkwy Ste.113 Lincolnshire, IL 60069

Tel: +1 847-913-6878

Fax: +1 847-913-6879

E-mail: office@kemaico.us

info@kemaico.us

Web: www.kemaico.us